

Section I. Product Identification and Uses

HMIS (HFRP)
Health Hazard 2
Fire Hazard 4
Reactivity 1
Personal Protection b

Common / Trade name	EXIT2 GUM REMOVER	TDG	Class 2.1: Flammable gas.
WHMIS	A, B5, D2B	PIN	UN1950 AEROSOLS
Code	2053	PG	X
Material uses	Industrial applications: Chewing gum remover		

Section II. Hazardous Ingredients

Name	CAS #	% by weight	TLV/PEL	LC50/LD50
LIQUIFIED PETROLEUM GAS	68476-85-7	60-100	Not available.	Not available.
Ethyl alcohol	64-17-5	5 - 10	Not available.	ORAL (LD50): Acute: 8300 mg/kg [Mouse]. 13700 mg/kg [Rat]. 17750 mg/kg [Rat].

Section III. First Aid Measures

Eye contact Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin contact In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion Not applicable (gas).

Section IV. Physical Data

Physical state and appearance	Liquid.	Colour	Colorless.
pH (1% soln/water)	Not available.	Odour	Cherry.
pH (concentrate)	Not available.	Volatility	Not available.
Boiling point	Not available.	Vapour density	> 1 (Air = 1)
Specific gravity	0.57 (Water = 1)	Vapour pressure	The highest known value is 5.7 kPa (43 mm Hg) (at 20°C) ().
Solubility	Not available		

Section V. Fire and Explosion Data

The product is Flammable.

Auto-ignition temperature Not available.

Flash points Closed cup: 12.8 C (55.04 F)

Degradation products These products are carbon oxides (CO, CO²).

Extinguishing media SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

Section VI. Reactivity data

Stability The product is stable.

Decomp. products See fire degradation products.

Reactivity Incompatible with strong oxidizing agents, bases, acids, silver salts, metal hydrides, alkali.

Section VII. Toxicological properties

Route of entry Skin. Eye contact. Inhalation. Ingestion.

Toxicity for animals Not available.

Acute effects May cause eye irritation. May cause burning sensation, redness, and pain. May cause skin irritation. Prolonged exposure may cause skin defatting. Inhalation of vapors may cause dizziness, an irregular heartbeat, nausea or asphyxiation.

Chronic effects Repeated or prolonged exposure to the ethanol can produce liver damage.

Section VIII. Preventive measure

Waste disposal According to federal, provincial and local regulations

Storage Keep container in a cool, well-ventilated area. Keep away from heat, sparks and flame.

Precautions Keep away from sources of ignition. Do not breathe gas/fumes/ vapor/spray. Take precautionary measures against electrostatic discharges. Avoid contact with skin and eyes.

Spill and leak Remove all sources of ignition and ventilate area. Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Section IX. Personal protective equipment

Gloves Gloves (impervious) are recommended for prolonged contact with bulk quantities.

Respiratory Wear appropriate respirator when ventilation is inadequate.

Eyes Splash goggles.

Other Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Eng. controls Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Section X. Preparation and other Information

Validated by the Regulatory Affairs Department on 23 Dec. 2008

Printed 17 May 2010

EMERGENCY: EMERGENCY: CANUTEC 613-996-6666

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex A. Legend

HMIS Hazardous Materials Identification System

WHMIS WHMIS Workplace Hazardous Materials Information System

TDG Transport Dangerous Goods

PIN Product Identification Number

PG Packaging Group
